

Patent



APPLICATION FOR UNITED STATES LETTERS PATENT

for

SCHEME FOR MERGING PARTIALLY FILLED ATM CELLS

Inventors:
David A. Hughes
Alan Saldinger

Prepared by:
BLAKELY, SOKOLOFF, TAYLOR & ZAFMAN
12400 Wilshire Boulevard
Seventh Floor
Los Angeles, California 90025-1026
(408) 720-8598

Attorney Docket No. 81862.P072

'EXPRESS MAIL' MAILING LABEL NUMBER EM56411534045

DATE OF DEPOSIT MARCH 28, 1997

**I HEREBY CERTIFY THAT THIS PAPER OR FEE IS BEING DEPOSITED
WITH THE UNITED STATES POSTAL SERVICE 'EXPRESS MAIL POST
OFFICE TO ADDRESSEE' SERVICE UNDER 37CFR 1.10 ON THE DATE
INDICATED ABOVE AND IS ADDRESSED TO THE ASSISTANT
COMMISSIONER FOR PATENTS, WASHINGTON, D.C. 20231**

Lisa Kaiser

(TYPED OR PRINTED NAME OF PERSON MAILING PAPER OR FEE)

Lisa Kaiser

(SIGNATURE OF PERSON MAILING PAPER OR FEE)

08825492 032897

SCHEME FOR MERGING PARTIALLY FILLED ATM CELLS

FIELD OF THE INVENTION

5 The present invention relates generally to the field of cell switching network communications and, more specifically, to the merging of data information contained in multiple partially filled cells transported across such a network into a single cell to enable efficient use of available bandwidth.

BACKGROUND

 The desire to integrate data, voice, image and video over high speed digital trunks has led to the development of a variety of packet and cell switching techniques. One such technique is called Asynchronous Transfer Mode (ATM). ATM is a switching technology that provides users with the ability to connect to one or more users in a transparent fashion.

15 Unlike the variable length packets used by frame relay services, ATM service is based on switching fixed length packets of data known as cells. Cell switching, as it is called, is gaining popularity for a variety of reasons. First, switch architectures can be optimized to switch cells at much higher speeds than variable length packets. Second, multiple services requiring a variety of quality of service guarantees can be provided simultaneously. ATM

20 user traffic is first segmented into fixed length cells, transmitted, then reassembled back into its original form. This segmentation and reassembly (SAR) process is done in a standardized way, regardless of the carrier providing the ATM service.

 Although the use of fixed length cells in ATM can be efficient in terms of allowing standardized switching apparatus to be used, for many applications the standard 53-byte

25 cell provides too large a package for the data requiring transport through the network. As a result, much of the cell payload is merely "padding" and the transport of such padding

wastes the available bandwidth of the ATM network. Several approaches to solve this problem present themselves.

For example, one could use a shorter length cell. As indicated, ATM uses a standard 53-byte cell, with 48-bytes of payload and 5-bytes of header information.

- 5 Choosing a smaller cell size could result in less of the cell payload being filled by padding. However, shorter cells have two important disadvantages. First, such cells would be non-standard and, as a result, such cells could not be transported through ATM networks designed to accommodate only standard size cells. This lack of interoperability would likely mean that users would be disinclined to accept such a solution. Second, smaller cells
- 10 would likely end up wasting more bandwidth than they would save because the ratio of header size to payload is much higher than for a 53-byte cell. Unfortunately, the header size could probably not be reduced from the current 5-byte size without a loss of functionality.

- Another solution might be to use variable length packets, as is common in frame
- 15 relay networks. This could conceivably avoid the need for padding altogether because packets could be "custom built" to the requirements of the user data. Unfortunately, the very fact that such varying packet sizes are allowed within frame relay networks means that the switches used to transport the packets across the network must be more complex than their ATM counterparts. As a result, such switches are generally slower than ATM
- 20 switches. Further, in networks where variable length packets are used, it is difficult to make real time service guarantees without the use of complex servicing and queuing algorithms and some limitations on packet size.

- Yet another solution might be to pack multiple payloads into one cell at a source and then pull these payloads apart at a destination. The ATM Forum has begun discussions
- 25 regarding such bundling of data channels within a single cell, however, it is recognized that this will only provide a solution for channels which have the same source and destination nodes. For example, referring to Figure 1, multiple calls from end-system A to end-system

B could be bundled together, but such calls could not be bundled with calls from end-system C to end-system D, even though they share a network trunk between switches 5 and 10. This results in less than ideal efficiency and also requires higher layer signaling support to assign slots in each cell to various channels and to manage the slot allocation across a network. Possibly, switches 5 and 10 could provide a server functionality which terminates all virtual channels (VCs) and swaps around sub-channels to improve efficiency on the network link between the switches. However, this solution would introduce significant complexity in switches 5 and 10 because the switches would now be required to understand the end-to-end channel assignments and pack and unpack data from many cells simultaneously. Besides the increased hardware complexity required for this function, the signaling and management of the reassignment of sub-channels would require complicated signaling.

Accordingly, what is needed is a scheme for ensuring that as much available payload space within the fixed length cells of ATM networks are used to transport user data rather than padding without resulting in the drawbacks of the methods described above.

SUMMARY AND OBJECTS OF THE INVENTION

It is, therefore, an object of the present invention to provide a method for merging two or more partially filled ATM cells into one merged ATM cell.

It is an additional object of the present invention to allow for splitting payload data
5 in a merged ATM cell into two or more partially filled ATM cells.

These and other objects of the invention are achieved, in one embodiment, in a method for merging partially filled ATM cells in which first and second partially filled ATM cells are removed from a cell stream and merged into a third ATM cell. The third ATM cell may then be inserted back into the cell stream. The third ATM cell may include header
10 information indicative of the number of partially filled ATM cells from which it was created.

In a further embodiment, a data communication device, such as an ATM switch, includes means for identifying partially filled ATM cells within an ATM cell stream. The device also includes means for merging at least two of the partially filled ATM cells into a
15 merged ATM cell and means for inserting the merged ATM cell back into the ATM cell stream. The means for identifying partially filled ATM cells may comprise a lookup table stored in a computer readable medium and indexable using logical connection identification (e.g., VC) information.

The present invention can be used on a link-by-link basis within an ATM network
20 or across multiple hops within such a network for combining cells traveling along a common route. The present invention is not limited to combining information on the same virtual channel or information which travels only between a common source and destination. The method maintains the use of standard ATM cells and so is compatible with existing and future ATM equipment. Other objects, features and advantages of the present
25 invention will be apparent from the accompanying drawings and from the detailed description which follows.

BRIEF DESCRIPTION OF THE DRAWINGS

The present invention is illustrated by way of example and not limitation in the figures of the accompanying drawings, in which like references indicate similar elements, and in which:

5 Figure 1 illustrates a cell relay network having four end-stations and two switches with multiple calls routed between various end-stations;

 Figure 2 illustrates the merging of two partially filled ATM cells into a single merged ATM cell according to one embodiment of the present invention;

 Figure 3 illustrates the use of cell splitting and merging functions within various
10 nodes of an ATM network according to one embodiment of the present invention; and

 Figure 4 illustrates the use of cell splitting and merging functions within end-nodes of an ATM network according to one embodiment of the present invention.

20330-0645380

DETAILED DESCRIPTION

A method and apparatus to allow merging/splitting of partially filled ATM cells into/from a single merged ATM cell is described. According to one embodiment, partially filled ATM cells passing through a node of an ATM network are removed from an ATM cell stream and merged into a single ATM cell. The single, merged ATM cell may then be inserted back into the cell stream. Header information in the single, merged cell may be used to indicate the number of partially filled cells which were used to construct the single, merged cell.

As shown in Figures 2-4, a means of combining payloads on different virtual channels (VCs) into a single cell is provided. A "merging" function is provided at a transmitting end of a link in an ATM network and a "splitting" function is provided at the receiving end of the link. These functions are provided below the ATM layer so that the operations are transparent to switches (such as switches 15 and 20 in Figures 3 and 4), end-systems (such as systems A, B, C and D in Figures 3 and 4) and signaling and application software.

Figure 2 illustrates the essence of the merging and splitting functions provided at the ends of a transmission link. Partially filled ATM cells 30 and 32 are removed from a cell stream 34 at any node (e.g., a switch or and end-system) of an ATM network. The cell stream 34 also includes filled cells 36. The partially filled cells 30 and 32 are merged together (headers and payloads) into a single merged ATM cell 38 with a new header 40, and the new merged cell 38 is then reinserted back into the cell stream 34. Figure 2 shows the case where two partially filled cells are merged into a single cell, however, it should be appreciated that other numbers of cells could be similarly merged, so long as the resulting cell maintains the 53-byte size of a standard ATM cell. Header 40 contains all of the information necessary to reconstruct the original cells 30 and 32 at a receiving end. This may include, for example, the number of partial cells contained in the merged cell,

delineation information indicating the boundaries of the original cells in the merged cell, etc.

The merging algorithm works by holding a first partially filled cell until the next partially filled cell arrives. The user data and headers from the two partially filled cells are then merged into a single cell. If the second partially filled cell does not arrive within a preset time interval, then the first partially filled cell could be reinserted back into the cell stream unaltered so as to avoid lengthy delays and/or out-of-order cell transmission. During reception, a splitting algorithm recognizes (e.g., from the header information) a merged cell and splits the payloads and headers of the two partially filled cells back into separate cells which are then reinserted in the cell stream.

Many different merging schemes could be used. For example, a simple system might have fixed positions for n , 48/ n -byte sub-cells. That is, if n represents the number of partially filled ATM cells to be merged into a single cell ($n = 2$ in Figure 2), then a system could allocate fixed positions for n such cells, each having 48/ n bytes, within the single merged cell to be produced (e.g., $48/2 = 2 \times 24$ -byte cells for the example shown in Figure 2).

A more elaborate indexing scheme for multiple sub-cells of different lengths could also be used. In such a scheme, payload byte 1 of the merged cell might accommodate the length, l_1 , of partially filled cell 1 (user data and header); payload bytes 2 to l_1+1 would then carry cell 1; payload byte l_1+2 would accommodate the length of cell 2; payload bytes l_1+3 to l_1+l_2+2 would then contain cell 2; and so on. To improve packing efficiency in either of these schemes, the header error correction (HEC) byte in the merged headers may be dropped. Also, it may be desirable to limit the VPI/VCI space in the merged cell headers to less than 28 bits. To provide protection, an error control byte for the entire merged cell could be provided.

The VCI of the merged cell (shown as $VCI = c$ in Figure 2, where the partially filled cell 30 had original $VCI = a$ and partially filled cell 32 had original $VCI = b$) could be

used to represent the merging method. Thus, multiple merging methods could be supported on a single link. For example, VCI = 32 could be used to indicate that two cells are merged while VCI = 33 could be used to indicate that three cells are merged, and so on.

When the cells are split at the receiving end, the unused bytes in the resulting
5 partially filled cells must be padded. The value or method used for padding could be indicated by the VCI or conveyed as a coding in the merged cell payload.

The splitting and merging functions described above may be part of the physical convergence sub-layer so that the functions are transparent to the layers above. The functions can be deployed on a link by link basis within a network. As shown in Figure 3,
10 any short payload traffic traveling on the link between switches 15 and 20 could be merged, regardless of the end-to-end path. Similarly, any traffic on the link between end-system C and switch 15 could also be merged, regardless of the end-to-end path. Notice that where link by link merging and splitting is performed, the end-nodes of the merging/splitting operation carry out complementary functions. That is, for traffic between
15 switches 15 and 20, if a merging operation is performed at switch 15, a complementary splitting operation is performed at switch 20, and vice-versa. Also, if a merging function is performed at end-system C, a splitting function will be performed at switch 15, and so on. Traffic on other links in the network illustrated in Figure 3 would travel as in a conventional ATM system.

20 As extensions of the example illustrated in Figure 3, the splitting/merging operations may be used to operate over virtual links, i.e., virtual paths (VPs) tunneled through switches without the merging or splitting functions. Note that for this approach, only cells traveling through the same tunnel can be merged. This could be identified by matching VPs or by use of a unique cell tag match, internal to the switches or end-systems.

25 Alternatively, the merging/splitting operations could be provided only on an end-to-end basis, if it is possible to identify which VCs are traveling on a common path. An example of this approach is illustrated in Figure 4. End-systems B and C are configured

with means to provide merging and splitting operations as described above. Traffic between end-systems B and C is passed between switches 15 and 20, neither of which are configured to provide merging/splitting operations. Merged traffic between end-systems B and C is passed between switches 15 and 20 in the same manner as any other ATM traffic because the merged cells maintain the standard ATM cell profile. When the merged cells reach a destination end-system, a splitting operation is performed and individual, partially filled cells are created. This example applies to cells traveling on the same end-to-end path, which could be identified using a cell tag match system internal to the end-systems.

It should be appreciated that the merging and splitting functions could reside at the inputs and outputs of a switch, be incorporated into a switch, or reside in an adjunct server module. However resident, the operations require a means to identify which cells are partially filled. This could be achieved in a variety of ways. For example, a table of bits (e.g., a lookup table) indexed by connection number or VCI/VPI indicating whether or not a connection can be compressed (i.e., merged). This would be suitable for applications such as compressed voice where virtually every cell contains only a partially filled payload. Alternatively, a new PTI (e.g., PTI = 7) could be used to convey that the cell has a partially filled payload and is eligible for a merging operation. Further, partially filled cells could be identified by looking at AAL information, e.g., finding single cell AAL5 frames. Of course, other means of identifying partially filled cells are possible.

It will be appreciated that the merging and splitting operations could violate cell sequence integrity when a single virtual channel contains some partially filled cells and some fully packed cells. This can occur, for example, when partially filled cells are removed from a cell stream, e.g., in a switch, and a fully packed cell on the same virtual channel is passed while the partially filled cell is held, awaiting another partially filled cell to arrive. This problem can be avoided by checking for a match between the VPI/VCI of waiting partially filled cells and the VCI/VPI of fully packed cells which are passing by. When a match is detected, the partially filled cell(s) having the matching VCI/VPI is/are

reinserted into the cell stream and scheduled before the fully packed cell, to avoid cell out-of-order transmission.

The merging/splitting operations discussed above improve the efficiency of the transport of short pieces of data while retaining the benefits of the ATM standard cell size.

5 For compressed voice applications, it is believed that these operations can achieve transport efficiency over existing methods on the order of 2 to 4 times. Existing and future standard ATM switches and end-systems can accommodate these merging and splitting operations because the operations are transparent to the ATM level. The methods may be employed on a link by link basis and, therefore, there is no need for a network-wide equipment upgrade
10 when some components are configured in accordance with the present invention. It is recognized that these methods may require a switch core to drive a merging unit and/or accept cells from a splitting unit at up to "n" times the link rate (where n = the number of partially filled cells to be merged into a single, merged cell). This may cause the apparent link capacity to fluctuate depending on the compression efficiency. However, this situation
15 should not present a problem for lower speed links where compression efficiency is generally most important.

Thus, a method and apparatus for merging/splitting partially filled ATM cells into/from a single, merged ATM cell has been described. In the foregoing specification, the invention has been described with reference to specific exemplary embodiments thereof.

20 It will, however, be clear that various modifications and changes may be made thereto without departing from the broader spirit and scope of the invention as set forth in the appended claims. The specification and drawings are, accordingly, to be regarded in an illustrative rather than a restrictive sense.

1 7. A method for merging partially filled ATM cells as in claim 5 wherein said steps of
2 removing a first partially filled ATM cell from an ATM cell stream; removing a second
3 partially filled ATM cell from the ATM cell stream; and merging the first partially filled
4 ATM cell and the second partially filled ATM cell into a third ATM cell are carried out in an
5 ATM end-system.

1 8. A method for merging partially filled ATM cells as in claim 5 further comprising the
2 step of transmitting the third ATM cell.

1 9. A data communication device, comprising:
2 means for identifying partially filled ATM cells within an ATM cell stream
3 associated with the device; and
4 means for removing partially filled ATM cells from the ATM cell stream coupled to
5 the means for identifying.

1 10. A data communication device as in claim 9, further comprising:
2 means for merging at least two partially filled ATM cells into a merged ATM cell
3 coupled to the means for removing.

1 11. A data communication device as in claim 10, further comprising:
2 means for inserting the merged ATM cell into the ATM cell stream coupled to the
3 means for merging.

1 12. A data communication device as in claim 11 wherein the means for identifying
2 comprises a lookup table stored in a computer readable format on a computer readable
3 medium and indexable using logical connection identification information from the ATM
4 cells within the ATM cell stream.

1 13. A data communication device as in claim 11, further comprising:
2 means for splitting a merged ATM cell into two or more partially filled ATM cells.

1 14. An ATM network, comprising:
2 a first node configured to identify partially filled ATM cells within an ATM cell
3 stream passing through the first node and to merge two or more of the partially filled ATM
4 cells in the cell stream into a merged cell; and
5 a second node coupled to the first node and configured to identify a merged ATM
6 cells and to split the merged ATM cell into two or more partially filled ATM cells.

1 15. An ATM network as in claim 14 wherein the first node is configured such that
2 circuitry in the first node performs the steps of:
3 removing a first partially filled ATM cell from the ATM cell stream;
4 removing a second partially filled ATM cell from the ATM cell stream; and
5 merging the first partially filled ATM cell and the second partially filled ATM cell
6 into a third ATM cell.

1 16. An ATM network as in claim 15 wherein the first node is further configured such
2 that circuitry in the first node performs the further step of:
3 inserting the third ATM cell into the ATM cell stream.

1 17. An ATM network as in claim 16 wherein said third ATM cell comprises header
2 information indicative of the number of partially filled ATM cells contained within the third
3 ATM cell.

1 18. An ATM network as in claim 16 wherein the third ATM cell is inserted into the
2 ATM cell stream so as to maintain correct cell ordering within the ATM cell stream.

1 19. An ATM network as in claim 16 wherein the first node is an ATM end-system.

1 20. An ATM network as in claim 16 wherein the first node is an ATM switch.

ABSTRACT

First and second partially filled ATM cells are removed from a cell stream and merged into a third ATM cell. The third ATM cell may then be inserted back into the cell stream. The third ATM cell may include header information indicative of the number of partially filled ATM cells from which it was created. To accommodate these operations, a data communication device, such as an ATM switch, includes means for identifying partially filled ATM cells within an ATM cell stream. The device also includes means for merging at least two of the partially filled ATM cells into a merged ATM cell and means for inserting the merged ATM cell back into the ATM cell stream. The means for identifying partially filled ATM cells may comprise a lookup table stored in a computer readable medium and indexable using logical connection identification information. The scheme can be used on a link-by-link basis within an ATM network or across multiple hops within such a network for combining cells traveling along a common route. The scheme is not limited to combining information on the same virtual channel or information which travels only between a common source and destination.




FIG. 1




FIG. 2




FIG. 3




FIG. 4

DECLARATION AND POWER OF ATTORNEY FOR PATENT APPLICATION

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below, next to my name.

I believe I am the original, first, and sole inventor (if only one name is listed below) or an original, first, and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled

"SCHEME FOR MERGING PARTIALLY FILLED ATM CELLS"

the specification of which

X is attached hereto.
_____ was filed on _____ as
_____ United States Application Number _____
or PCT International Application Number _____
and was amended on _____
(if applicable)

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claim(s), as amended by any amendment referred to above.

I acknowledge the duty to disclose all information known to me to be material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56.

I hereby claim foreign priority benefits under Title 35, United States Code, Section 119(a)-(d), of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed:

<u>Prior Foreign Application(s)</u>			<u>Priority Claimed</u>	
<u>(Number)</u>	<u>(Country)</u>	<u>(Day/Month/Year Filed)</u>	<u>Yes</u>	<u>No</u>
<u>(Number)</u>	<u>(Country)</u>	<u>(Day/Month/Year Filed)</u>	<u>Yes</u>	<u>No</u>
<u>(Number)</u>	<u>(Country)</u>	<u>(Day/Month/Year Filed)</u>	<u>Yes</u>	<u>No</u>

"Express Mail" mailing label number EM564153ADWS
 Date of Deposit MAR 28, 1997
 I hereby certify that the paper on which this document is deposited is of the United States Post Office Service "Express Mail" service under 37 CFR 1.10 and is addressed to the Assistant Commissioner for Patents, Washington, D.C. 20231

Rev. 10/01/96 (D2) cak

-1-

(Typed or name of person mailing paper or fee)
Liza Kaiser
(Signature of person mailing paper or fee)

I hereby claim the benefit under title 35, United States Code, Section 119(e) of any United States provisional application(s) listed below

(Application Number)	Filing Date
(Application Number)	Filing Date

I hereby claim the benefit under Title 35, United States Code, Section 120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, Section 112, I acknowledge the duty to disclose all information known to me to be material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56 which became available between the filing date of the prior application and the national or PCT international filing date of this application:

(Application Number)	Filing Date	(Status -- patented, pending, abandoned)
(Application Number)	Filing Date	(Status -- patented, pending, abandoned)

I hereby appoint Aloysius T. C. AuYeung, Reg. No. 35,432; William Thomas Babbitt, Reg. No. 39,591; Jordan Michael Becker, Reg. No. 39,602; Bradley J. Bereznak, Reg. No. 33,474; Michael A. Bernadicou, Reg. No. 35,934; Roger W. Blakely, Jr., Reg. No. 25,831; Gregory D. Caldwell, Reg. No. 39,926; Kent M. Chen, Reg. No. 39,630; Lawrence M. Cho, Reg. No. 39,942; Thomas M. Coester, Reg. No. 39,637; Roland B. Cortes, Reg. No. 39,152; William Donald Davis, Reg. No. 38,428; Daniel M. De Vos, Reg. No. 37,813; Karen L. Feisthamel, Reg. No. 40,264; David R. Halvorson, Reg. No. 33,395; Eric Ho, Reg. No. 39,711; George W Hoover II, Reg. No. 32,992; Eric S. Hyman, Reg. No. 30,139; Dag H. Johansen, Reg. No. 36,172; Stephen L. King, Reg. No. 19,180; Dolly M. Lee, Reg. No. 39,742; Michael J. Mallie, Reg. No. 36,591; Kimberley G. Nobles, Reg. No. 38,255; Ronald W. Reagin, Reg. No. 20,340; James H. Salter, Reg. No. 35,668; William W. Schaal, Reg. No. 39,018; James C. Scheller, Reg. No. 31,195; Maria McCormack Sobrino, Reg. No. 31,639; Stanley W. Sokoloff, Reg. No. 25,128; Allan T. Sponseller, Reg. No. 38,318; Steven R. Sponseller, Reg. No. 39,384; David R. Stevens, Reg. No. 38,626; Edwin H. Taylor, Reg. No. 25,129; Lester J. Vincent, Reg. No. 31,460; John Patrick Ward, Reg. No. 40,216; Ben J. Yorks, Reg. No. 33,609; and Norman Zafman, Reg. No. 26,250; my attorneys; and Gary B. Goates, Reg. No. 35,159; Michael Anthony DeSanctis, Reg. No. 39,957; Charles E. Shemwell, Reg. No. 40,171; Edwin A. Sloane, Reg. No. 34,728; and Judith A. Szepesi, Reg. No. 39,393; my patent agents, of BLAKELY, SOKOLOFF, TAYLOR & ZAFMAN LLP, with offices located at 12400 Wilshire Boulevard, 7th Floor, Los Angeles, California 90025, telephone (310) 207-3800, with full power of substitution and revocation, to prosecute this application and to transact all business in the Patent and Trademark Office connected herewith.

Send correspondence to Tarek N. Fahmi, BLAKELY, SOKOLOFF, TAYLOR &
(Name of Attorney or Agent)
ZAFMAN LLP, 12400 Wilshire Boulevard 7th Floor, Los Angeles, California 90025 and
direct telephone calls to Tarek N. Fahmi, (408) 720-8598.
(Name of Attorney or Agent)

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Full Name of Sole/First Inventor David A. Hughes

Inventor's Signature 

Date

3/25/97


Residence Mountain View, CA
(City, State)

Citizenship

New Zealand
(Country)

Post Office Address 900 High School Way, #2230
Mountain View, CA 96061

Full Name of Second/Joint Inventor Alan Saldinger

Inventor's Signature 

Date

3/24/97

Residence Los Altos, CA
(City, State)

Citizenship

U.S.A.
(Country)

Post Office Address 205 Galli Drive
Los Altos, California 94022

Title 37, Code of Federal Regulations, Section 1.56
Duty to Disclose Information Material to Patentability

(a) A patent by its very nature is affected with a public interest. The public interest is best served, and the most effective patent examination occurs when, at the time an application is being examined, the Office is aware of and evaluates the teachings of all information material to patentability. Each individual associated with the filing and prosecution of a patent application has a duty of candor and good faith in dealing with the Office, which includes a duty to disclose to the Office all information known to that individual to be material to patentability as defined in this section. The duty to disclose information exists with respect to each pending claim until the claim is cancelled or withdrawn from consideration, or the application becomes abandoned. Information material to the patentability of a claim that is cancelled or withdrawn from consideration need not be submitted if the information is not material to the patentability of any claim remaining under consideration in the application. There is no duty to submit information which is not material to the patentability of any existing claim. The duty to disclose all information known to be material to patentability is deemed to be satisfied if all information known to be material to patentability of any claim issued in a patent was cited by the Office or submitted to the Office in the manner prescribed by §§1.97(b)-(d) and 1.98. However, no patent will be granted on an application in connection with which fraud on the Office was practiced or attempted or the duty of disclosure was violated through bad faith or intentional misconduct. The Office encourages applicants to carefully examine:

(1) Prior art cited in search reports of a foreign patent office in a counterpart application, and

(2) The closest information over which individuals associated with the filing or prosecution of a patent application believe any pending claim patentably defines, to make sure that any material information contained therein is disclosed to the Office.

(b) Under this section, information is material to patentability when it is not cumulative to information already of record or being made of record in the application, and

(1) It establishes, by itself or in combination with other information, a prima facie case of unpatentability of a claim; or

(2) It refutes, or is inconsistent with, a position the applicant takes in:

(i) Opposing an argument of unpatentability relied on by the Office, or

(ii) Asserting an argument of patentability.

A prima facie case of unpatentability is established when the information compels a conclusion that a claim is unpatentable under the preponderance of evidence, burden-of-proof standard, giving each term in the claim its broadest reasonable construction consistent with the specification, and before any consideration is given to evidence which may be submitted in an attempt to establish a contrary conclusion of patentability.

(c) Individuals associated with the filing or prosecution of a patent application within the meaning of this section are:

(1) Each inventor named in the application;

(2) Each attorney or agent who prepares or prosecutes the application; and

(3) Every other person who is substantively involved in the preparation or prosecution of the application and who is associated with the inventor, with the assignee or with anyone to whom there is an obligation to assign the application.

(d) Individuals other than the attorney, agent or inventor may comply with this section by disclosing information to the attorney, agent, or inventor.